



RENEWABLE ENERGY PRODUCT LINE



MODEL	BCI	PLATES PER CELL	20 HR Rate	72 HR Rate	100 HR Rate	LENGTH Inches / cm	WIDTH Inches / cm	HEIGHT Inches / cm	WET WEIGHT lbs / kg	DRY WEIGHT lbs / kg	
Section A 2-Volt 1 Cell Polypropylene Container											
S-1380	7YR	EKG	43	1050	1323	13 3/8" 33.97 cm	7 1/8" 18.10 cm	17" 43.18 cm	115 lbs 52.16 kg	82 lbs 37.19 kg	
S-1590	7YR	EKG	49	1200	1512	13 3/8" 33.97 cm	7 1/8" 18.10 cm	17" 43.18 cm	121 lbs 54.88 kg	86 lbs 39.01 kg	
S-1725	7YR	EKG	53	1300	1638	13 3/8" 33.97 cm	7 1/8" 18.10 cm	17" 43.18 cm	125 lbs 56.70 kg	92 lbs 41.72 kg	
Section B 6-Volt 3 Cell Polypropylene Container											
S-460	7YR	EKG	15	350	441	12 1/2" 31.75 cm	7 1/8" 18.10 cm	16 3/4" 42.55 cm	108 lbs 48.99 kg	78 lbs 35.38 kg	
S-530	7YR	EKG	17	400	504	12 1/2" 31.75 cm	7 1/8" 18.10 cm	16 3/4" 42.55 cm	117 lbs 53.07 kg	90 lbs 40.82 kg	
S-600	7YR	EKG	19	450	567	12 1/2" 31.75 cm	7 1/8" 18.10 cm	16 3/4" 42.55 cm	122 lbs 55.34 kg	97 lbs 44.00 kg	
Section C 12-Volt 6 Cell Polypropylene Container											
24 HT 80	7YR	24	7	80	101	11" 27.94 cm	6 3/4" 17.15 cm	9 1/2" 24.13 cm	50 lbs 22.68 kg	38 lbs 17.24 kg	
27 HT 90	7YR	27	9	90	113	12 3/4" 31.75 cm	6 5/8" 16.83 cm	9 1/4" 23.50 cm	62 lbs 28.12 kg	46 lbs 20.87 kg	
27 HT 105	7YR	27	11	105	132	12 3/4" 31.75 cm	6 5/8" 16.83 cm	9 1/4" 23.50 cm	68 lbs 30.84 kg	52 lbs 23.59 kg	
T12 250	7YR	Spec	9	200	252	15 3/8" 39.05 cm	7" 17.78 cm	14 3/8" 36.51 cm	140 lbs 63.50 kg	97 lbs 44.00 kg	
Section D 2-Volt 1 Cell Dual Container											
2 KS 33P	10YR	Spec	33	1766	2349	2490	15 7/16" 39.21 cm	8 5/16" 21.11 cm	24 13/16" 63.02 cm	208 lbs 94.35 kg	145 lbs 65.78 kg
2 YS 31P	10YR	Spec	31	2430	3232	3426	15 1/2" 39.40 cm	9" 22.86 cm	31 5/8" 80.33 cm	285 lbs 129.27 kg	200 lbs 90.72 kg
Section E 4-Volt 2 Cell Dual Container											
4 CS 17P	10YR	Spec	17	546	726	770	14 3/8" 36.51 cm	8 1/4" 21.00 cm	18 1/4" 46.40 cm	128 lbs 58.06 kg	98 lbs 44.45 kg
4 KS 21P	10YR	Spec	21	1104	1468	1557	15 3/4" 40.00 cm	9 3/8" 23.81 cm	24 3/4" 62.87 cm	267 lbs 121.11 kg	216 lbs 97.98 kg
4 KS 25P	10YR	Spec	25	1350	1796	1904	15 3/4" 40.00 cm	10 5/8" 27.00 cm	24 3/4" 62.90 cm	315 lbs 142.88 kg	220 lbs 99.79 kg
All capacities based on specific gravities of 1.280. Reduce capacities 5% for 1.265 specific gravity and 10% for specific gravities of 1.250											

MODEL	BCI	PLATES PER CELL	20 HR Rate	72 HR Rate	100 HR Rate	LENGTH Inches / cm	WIDTH Inches / cm	HEIGHT Inches / cm	WET WEIGHT lbs / kg	DRY WEIGHT lbs / kg	
Section F 6-Volt 3 Cell Dual Container											
6 HHG 31P	7YR	Spec	31	344	433	458	20 3/4" 52.71 cm	8" 20.32 cm	11 7/8" 30.16 cm	125 lbs 56.70 kg	96 lbs 43.55 kg
6 EHG 31 P	7YR	Spec	31	410	517	545	20 3/4" 52.71 cm	8" 20.32 cm	12 3/4" 32.36 cm	133 lbs 60.32 kg	104 lbs 47.17 kg
6 CS 17P	10YR	Spec	17	546	726	770	22" 55.88 cm	8 1/4" 21.96 cm	18 1/4" 46.35 cm	221 lbs 100.24 kg	178 lbs 80.74 kg
6 CS 21P	10YR	Spec	21	683	908	963	22" 55.88 cm	9 3/4" 24.77 cm	18 1/4" 46.35 cm	271 lbs 122.92 kg	217 lbs 98.43 kg
6 CS 25P	10YR	Spec	25	820	1091	1156	22" 55.88 cm	11 1/4" 28.58 cm	18 1/4" 46.35 cm	318 lbs 144.24 kg	254 lbs 115.21 kg
Section G 8-Volt 4 Cell Dual Container											
8 HHG 31 P	7YR	8Volt	31	344	433	458	27" 68.58 cm	8" 20.32 cm	11 7/8" 30.16 cm	167 lbs 75.75 kg	128 lbs 58.06 kg
8 EHG 31 P	7YR	8Volt	31	410	517	545	27" 68.58 cm	8" 20.00 cm	12 3/4" 32.29 cm	178 lbs 80.74 kg	139 lbs 63.05 kg
8 CS 17P	10YR	8Volt	17	546	726	770	28 1/4" 71.76 cm	8 1/4" 20.96 cm	18 1/4" 46.36 cm	294 lbs 133.36 kg	238 lbs 107.95 kg
8 CS 25P	10YR	8Volt	25	820	1091	1156	28 1/4" 71.76 cm	11 1/4" 28.58 cm	18 1/4" 46.36 cm	424 lbs 192.32 kg	342 lbs 155.12 kg
Section H 12-Volt 6 Cell Dual Container											
12 CS 11P	10YR	Spec	11	357	475	503	22" 55.88 cm	11 1/4" 28.58 cm	18 1/4" 46.36 cm	272 lbs 123.38 kg	220 lbs 99.79 kg
All capacities based on specific gravities of 1.280. Reduce capacities 5% for 1.265 specific gravity and 10% for specific gravities of 1.250											



RENEWABLE ENERGY PRODUCT WARRANTY



We build one mean battery and we back them with comprehensive warranties that lead the industry in length of coverage. We're confident that our batteries will perform time after time, year after year. However, should a problem arise, you can be confident that you're covered better than any other battery warranty in the business.

Surrette Battery, herein referred to as the Company, warrants that batteries sold by it are merchantable and free of defects in workmanship and material at the time they are shipped from the Company's factory.

In the event that the Company makes a drop shipment to a distributor's customer, that customer must be instructed to perform an inspection of the goods BEFORE signing the delivery slip. The Company is not responsible for damaged product reported after shipment has been signed "Received in Good Condition".

ALL SHIPMENTS SHOULD BE THOROUGHLY INSPECTED FOR DAMAGE BEFORE SIGNING THE DELIVERY SLIP.

The Company will replace or, at its option, repair any Rolls Renewable Energy battery sold by it that fails to conform to the warranty stated below on a NO CHARGE BASIS as follows:

The Company makes no warranty with respect to its batteries other than the warranty stated below. All implied warranties of merchantability and all expressed and implied warranties of any other kind are hereby excluded.

SERIES 4000

Failure within 24 months from the date placed in service yields FREE REPLACEMENT, not including freight charges from the factory to the applicable destination. After the first 24 months of service, defective batteries will be adjusted for a period of up to 84 months prorated from the date first in service at prices in effect at time of adjustment.

SERIES 5000

Failure within 36 months from the date placed in service yields FREE REPLACEMENT, not including freight charges from the factory to the applicable destination. After the first 36 months of service, defective batteries will be adjusted for a period of up to 120 months prorated from the date first in service at prices in effect at time of adjustment.

To claim a manufacturing warranty, proof of purchase must be presented, showing the date of purchase and the battery's serial number. The battery must be tested by an Authorized Battery Outlet for actual defect, and upon confirmation of the defect, the warranty will be administered.

The Warranty does not cover shipping damage, cracked covers, cracked cases, bulged cases from heat, freezing or explosion, discharged batteries, the use of undersized batteries damaged from electrical equipment. This warranty covers only manufacturing defects.